



## SOFTWARE DEFINED RADIO

# Mobile **COMP@N**


Radio Communications  
of the Future



**VERSATILE**



**FLEXIBLE**



**CUSTOMIZED TO MISSION  
REQUIREMENTS**

### Wide range of functionalities:

- Basic e.g. voice transmissions broadcast
- Complex e.g. MANET radio / all available functions

Within the family of COMP@N radios it is possible to choose between different waveforms (WF) and range of supported frequencies.

Handheld COMP@N radios can be connected to the vehicle adapter and power amplifier to create mobile or stationary set.

Mobile adapter is a device which enables the use of COMP@N handheld radio in vehicles (e.g. light tanks, transporter vehicles). This set provides a secure attachment and a possibility for easy removing of the radio, without outages. After installing the radio in the adapter, it is being automatically switched to work with vehicular data communications system and power amplifier (if such is installed). In such set, a radio is powered via an adapter with the onboard network of the vehicle, while ensuring the charging of its battery from vehicular power supply. The adapter also provides an access to interfaces of the radio through a dedicated connectors, enabling further integration with on-board systems.

Mobile set, which consists of handheld COMP@N radio mounted in vehicular adapter, can be extended with power amplifier. It allows to work with maximum power 50 W, which significantly increase radio range. The amplifier is powered from the vehicular power supply and is designed for all the COMP@N family radios.

#### The basic parameters of the amplifier

frequency range	<b>30 -520 MHz</b>
input voltage	<b>17÷33 V</b>
maximum output power	<b>50 W</b>
dimensions	<b>270 x 180 x 187 mm</b>

The amplifier and adapter can be installed in the vehicle either as a separately mounted devices (e.g. spaced apart to several meters), and as one integrated set.

#### General specification of the COMP@N platform

FM/AM fixed frequency	modulations	FM, AM
	transmission modes	F3E, A3E
	channel	FM: 25 kHz
		AM: 8.33 kHz, 25 kHz
	Squelch	
	Nº of channels	1000
	Scan	
General	FCS (free channels search)	
	a large color display	
	auto backlight intensity regulation	
	menu	
	double PTT button	
	backlit keyboard	
	Emergency Clear button	
	build-in GPS receiver	
	dimensions (with amplifier & adapter)	270 x 180 x 277 mm
	weight	~ 15 kg
RF	frequency range	30÷520 MHz
	output power	up to 50 W
	suppression of harmonics:	> 50 dBc
	frequency stability:	± 1 ppm
	sensitivity:	- 116 dBm (SINAD 20 dB)
Interfaces	adjacent channel selectivity	≥ 50 dB
	Audio / PTT	
	RS232	
	Ethernet 10/100	
	USB	
	Side Connector (to work with COMP@N accesories)	
Enviromental parameters	operational temperature	-32°C ÷ +55°C
	MIL-STD-810G	
	EMC MIL-STD-461F	



## COMP@N H07 Waveforms

<b>DV</b>	operating modes	FH (Frequency Hopping): 100 hop/s
		FF (Fixed Frequency)
	digital voice transmission	
	channel	25 kHz
security (AES-256 based)	TRANSEC	
	COMSEC	
	Pre-defined profiles with set of mission parameters (radio data, encryption keys)	
<b>RSD</b>	channel	25 kHz
	capability to enter data via Ethernet or serial port	
	capability to transmit GPS reports	
modulation	$\pi/4$ DQPSK	
data rate	up to 40 kb/s	

## COMP@N H08 Waveforms

<b>W2FH</b>	EPM (Electronic Protective Measures) class waveform	LPD (Low Probability of Detection)
		LPI (Low Probability of Interception)
		AJ (Anti-Jamming)
operating modes	FH (Frequency Hopping): 300 hop/s	
	FF (Fixed Frequency)	
services	digital voice (e.g. MELPe 2400, CODEC2)	
	SA (Situation Awareness) messages and GPS reports	
	data (e.g. serial data, sensor data)	
	simultaneous transmission of voice, data and SA/GPS messages	
	SA (Situation Awareness) data and GPS data can be attached to each transmission of voice and data	
	synchronization without GNSS (e.g. GPS)	
	Radio Silence mode	
modulation	CPM	
channel	25 kHz with possible extension	
security (AES-256 based)	TRANSEC	
	COMSEC	
data rates	up to 26 kb/s	
	definable frequency range and sub-bands	
	pre-defined W2FH profiles with set of mission parameters (radio data, encryption keys)	

## COMP@N H09 Waveforms

<b>BMS IP WF</b>	MANET class waveform	mobile self-configuring and self-organizing network
		extended range of services (retransmission within waveform – multihop relay)
operating modes	FH (Frequency Hopping)	
	FF (Fixed Frequency)	
	operation in IP networks, build-in IP router, QoS supporting	
	simultaneous voice and data services	
voice services	digital voice (np. MELPe 2400, CODEC2)	
	group calls	
	privileged users	
	priority calls (break-in)	
	double PTT	
	multi-hop voice	
data services	IP data	
	Serial data	
	SA (Situation Awareness) messages	
	GPS reports	
	short text messages	
	sensor data	
	files, video, pictures, mail transmission supporting	
	data retransmission	
	synchronization without GNSS (e.g. GPS)	
modulation	CPM	
channel	50 kHz	
security (AES-256 based)	TRANSEC	
	COMSEC	
	NETSEC	
data rates	up to 40 kb/s	
	definable frequency range and sub-bands	
	pre-defined BMS IP WF profiles with set of mission parameters (radio data, encryption keys)	
	sms	
number of networks	20	



Mobile adapter with radio



Power amplifier



External loudspeaker



Handset

[www.wbgroup.pl](http://www.wbgroup.pl)

**RADMOR**  
WB GROUP

The information in this folder is not intended to constitute an offer within the meaning of the Civil Code.

RADMOR S.A.  
ul. Hutnicza 3, 81-212 Gdynia, Polska  
t: +48 58 7655 621 | f: +48 58 7655 662  
[market@radmor.com.pl](mailto:market@radmor.com.pl)

QIII/2020