

MK1 CENTRAL UNIT LITE

MK1 CU Lite shares the same core technology as our MK1 Central Unit, but has been optimized for voice only communications between crew member and a wide range of tactical radio systems.

The MK1 CU Lite is a cost effective version of Central Unit equipped with a range of interfaces allowing for cooperation with the devices incorporated into a combat military vehicle equipment and with terminals of the FONET system. It is responsible for digital voice communications and data transmission between integrated means of communications, superior officers etc.

- **4 FONET Line Interfaces and remote control**
- **2 Radio Interfaces (audio and PTT)**
- **Asynchronous Data Port w/ power output for GPS**
- **Speaker and Power output**




MK1 Central Unit Lite can run other applications like data exchange protocols, including VoIP or radio related functions like parameters remote setting or TDMA control.

wbgroupamerica.com

WB GROUP

AMERICA

WB Group America
1800 Diagonal Road Suite 600
Alexandria, Virginia 22314
t: +1 577 366 1772



Technical specifications

| | |
|-------------------------------|--|
| Operating system | WB Linux |
| Power consumption | 25 W (without external devices) |
| Power supply | 18 ÷ 36 V DC |
| Operating temperature range | -32°C ÷ +55°C |
| Storage temperature range | -50°C ÷ +70°C |
| Electromagnetic compatibility | MIL-STD-461 F |
| Environment requirement | MIL-STD-810 G |
| Shock / vibration | Tracked and wheeled vehicle |
| Dimensions | 262 [L] x 142 [W] x 85 [H] mm |
| Weight | ~2.2 kg (4,7 with shock mount) |